

MP 280 Lite

2" Mobile Thermal Receipt Printer



- Bluetooth Connectivity V4.0+USB
- Bluetooth pairing-Auto Reconnect
- Easy Paper Loading
- Light weight & Easy to Operate



Retail



Micro Finance



Parking lots



Field Force Automation



MP 280 Lite

2" Mobile Thermal Receipt Printer



Specification	MP 280 Lite
Print method	Thermal Line Printing
Print speed	70mm/sec
Print resolution	203 dpi
Print width	up to 48mm
sensor	Paper end : reflective sensor
Media characteristics	
Media type	Receipt
Media Width	58mm
Media roll diameter	upto 40mm
Media thickness	60 to 100µm
Supply method	Easy paper loading
Physical characteristics	
Dimension	115mm*84mm*38mm
Weight	265g
Environmental characteristics	
Operating temperature	-10°C-50°C
Storage temperature	-20°C-60°C
Fonts/Graphics/Symbolises	
Character size	12*24 dot font
Character per line	24 characters/line 32 characters/line 42 characters/line
Character sets	Alpha-numeric : 95 Expanded graphics: 128*33 page
Instruction set	ESC/POS compatible

For enquiries contact

☎ 9945003176 / 9945605979 | ✉ srinivas@annatechinc.com

Visit us : www.annatechinc.com