

Fast & Reliable Printing for Retail and Business Needs

Designed for Business,
Built for Speed




RP4230

4 - Inch Thermal Receipt Printer


Engineered for Retail & Logistics Efficiency



QR CODE



EASY LOAD



COMPACT
DESIGN



HIGH SPEED



Model	RP 4230
Printing method	Direct thermal
Paper width	115±0.5mm
Print width	48mm-108mm
Column capacity	864 dots/line
Printing speed	230mm/s
Interface	USB+Ethernet (Standard), USB+Ethernet+Bluetooth/USB+Ethernet+WiFi (Optional)
Line spacing	3.75mm(Adjustable by command)
Paper type	Continuous paper
Paper thickness	0.06-0.08mm
Paper roll outer diameter	101mm±0.5mm
Character size	ANK, Font A: 1.5x3.0mm(12x24 dots)Font B: 1.1x2.1mm(9x17 dots) Simplified/Traditional Chinese: 3.0x3.0mm(24x24 dots)
Barcode Character	
Extension character sheet	PC347 Standard Europe, Katakana, PC850 Multilingual, PC860 Portuguese, PC863 Canadian-French, PC865 Nordic, West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 Cyrillic#2, PC852 Latin2, Pc858, IranII, Latvian, Arabic, PT151(1251)
1D Barcode	1D:UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/TF/CODABAR/CODE93/CODE128
2D Barcode	2D:QR CODE/PDF417
Input buffer	4096Kbytes
NV Flash	256Kbytes
Power	
Power adaptor	Input: AC 100-240V 50~60Hz export: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	1.68kg
Dimensions	178*215*155mm (W*D*H)
Environmental Conditions	
Work environment	Temperature(0~45°C)humidity(10~80%) no condensing
Storage environment	Temperature(-10~60°C)humidity(10~90%)
Reliability	
Auto cutter	Full cut
Cutter life	1 million cuts
Printer Mechanism life	100 km
Software	
Emulation	ESC/POS
Driver	Windows, Linux, macOS, Android, OPOS, JavaPOS

For trade enquiries contact

Mob : 9945003176 / 7022544445 | Mail us : yashas@annatechinc.com

Address : 2nd Floor, No.48/2, R.V Rd, Opposite Metro Pillor No-82,
Basavanagudi, Bengaluru, Karnataka 560004

Visit us : www.annatechinc.com